

# MOTOMAN PL80

# Palletizing with the PL-series



The smallest palletizing robot in the MOTOMAN PL-series offers top performance with its 5 axes for box, carton and pack palletizing in end-of-line packaging and logistics applications.

The extended vertical reach of 3,291 mm ensures high palletizing heights, in combination with its horizontal reach of 2,061 mm, this enables a wide range of applications. The compact MOTOMAN PL80 guarantees high palletizing loads of up to 80 kg and impresses with its low overall height, slim design and small footprint.

The MOTOMAN PL80 is equipped with the latest Yaskawa Sigma7 Drive Technology and the compact YRC1000 high performance controller.

Ideal is the combination with the optional Functional Safety Unit (FSU) for safeguarding compact working areas, or with MotoLogix<sup>®</sup> for easy programming of the robot via PLC function blocks.

## **KEY BENEFITS**

- New Sigma7 servo motors → high accelerations, speed, energy efficiency
- High payload: max. 80 kg
- Large working range: 2,061 mm
- Compact and slim design
- Advanced functional safety (FSU) with YRC1000 controller
- Programmable by PLC function blocks via MotoLogix software interface
- Dust and liquid proof wrist design (IP54/67)



# **MOTOMAN PL80**

Media connector

234 234

346 203









Specifications PL80						
Axes	Maximum motion range [°]	Maximum speed [°/s]	Allowable moment [Nm]	Allowable moment of inertia [kg · m²]	Controlled axes	5
					Max. payload [kg]	80
S	±180	180	-	-	Repeatability [mm]	±0,03
L	+135/-90	180	-	-	Max. working range R [mm]	2061
U	+35/-160	180	-	-	Temperature [°C]	0 to +45
R	-	-	-	-	Humidity [%]	20 - 80
В	±15	180	78.5	48	Weight [kg]	565
т	±360	500	20.5	25	Max. connected load [kVA]	4.5

### Yaskawa Europe GmbH

**Robotics Division** Yaskawastraße 1 85391 Allershausen Germany

Tel. +49 (0) 8166 90-0 robotics@yaskawa.eu.com www.yaskawa.eu.com

All drawing dimensions in mm. Technical data may be subject to change without previous notice. Please request detailed drawings at robotics@yaskawa.eu.com.

View A



### View B



Media connector

View C



Mounting option: Floor IP Protection: IP54 (body), IP67 (wrist)

> YR-1-05VX80-A00 B-10-2021, A-No. 220139

YASKAWA